

AUTOTROL 263 & 268

RESIDENTIAL PERFORMA CONTROL VALVES



FEATURES/BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Designed with double backwash for reduced hardness leakage

Fully adjustable 5 or 8 cycle control for efficient and reliable water treatment system

Continuous service flow rate of 25 GPM with a backwash of 20 GPM

Backwash capability accommodates softener tanks up to 16" and filter up to 18" in diameter

Super capacitor for keeping time of day during power outage

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Soft water refill for a cleaner brine tank

Programming stored in memory and will not be lost due to power outages

History data for valve performance

OPTIONS

Filter or softener control valves

Fiber-reinforced polymer bypass valve

Plumbing connections in .75"-1.25" NPT, BSP, and sweat

Internal Autotrol turbine

Variable reserve for increased efficiency

Auxiliary switch kits

Timer wall mount kits

740- Simple economic electronic time clock control.

764- Professional level metered control with fully programmable cycle times and salt amount for multiple tank applications.

760- Simple economic electronic meter control.

742- Professional level time clock control with fully programmable cycle times and salt amount.

762- Professional level metered control with fully programmable cycle times and salt amount.

460i - 3 settings for metered control

460TC - 3 settings for time clock control



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

| | |
|---------------------------|----------------------------|
| Valve Body | Glass-filled thermoplastic |
| Rubber Components | Compounded for cold water |
| Weight (Valve & Control) | 5.3 lbs (2.4 kg) |
| Operating Pressure | 20-120 psi (1.38-8.27 bar) |
| Canada: | 20-100 psi (1.38-6.89 bar) |
| Hydrostatic Test Pressure | 300 psi (20.69) |
| Water Temperature | 35°-100°F (2°-38°C) |
| Ambient Temperature | 35°-120°F (2°-48.9°C) |

*Recommend use of outdoor cover for direct sunlight applications

ELECTRICAL

| | |
|------------------------|-----------------|
| Controller | |
| Operating Voltage | 12 volt- AC |
| Input Supply Frequency | 50 or 60 Hz |
| Moter Input Voltage | 12 volt- AC |
| Controller System | |
| Power Consumption | 3 watts average |

TRANSFORMER- ALL CONTROLLERS

| | |
|----------------------------|--|
| Transformer Output Voltage | 12 volt- AC 400mA |
| Transformer Input Options | 115 volt- AC 50/60 Hz 230 volt- AC 50/60 Hz 100 volt- AC 50/60 Hz |
| Transformer Plug Options | Indoor North American Plug Outdoor North American Plug Japanese Plug Taiwan/Korea Plug Australian Plug United Kingdown Plug Mainland Europe Plug |

VALVE CONNECTIONS

| | |
|----------------------|-----------------------|
| Tank Thread | 2-1/2" - 8, male |
| Inlet/Outlet Threads | 1-3/4"-12 UNC-2A male |
| Drain Line | 3/3" NPT, male |
| Brine Line | 3/8" NPT, male |

DIMENSIONS

| | |
|-----------------|-----------------------------------|
| Width | 14.9" (37.8 cm) |
| Height | 8.5" (21.5 cm) |
| Riser Tube Dia. | 1.050" (27 mm) |
| Riser Height | Above top of tank 0.5" (+/- 0.5") |

FLOW RATE

| | |
|------------------------|----------------------------------|
| Service | |
| 15 psi (1.03 bar) drop | 25.0 gpm (5.7 m ³ /h) |
| Backwash | |
| 25psi (1.72 Bar) drop | 20.0 gpm (4.5 m ³ /h) |
| Service | Cv = 6.50 (Kv = 5.6) |
| Backwash | Cv = 4.00 (Kv = 3.5) |



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com
© 2018 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

1223489 REV J JL18